

CDM8240

Bundle Dispensing Module
Maximum performance,
minimal costs



Description

The CDM8240 bundle dispensing module -the fruit of years of research and development- is a market leading cash dispensing module of which GRGBanking possesses full independent intellectual property rights. As a combination of advanced functionalities and a low cost of ownership, the CDM8240 offers superior performance and high reliability whilst it is easy to operate and maintain. All this and more makes the CDM8240 an ideal solution for ATMs and other self-service application.

CDM8240

Bundle Dispensing Module
Maximum performance, minimal costs

CDM8240 bundle dispensing module provides 4 advanced features of GRG's leading technology with all independent intellectual property rights owned by GRG.

Reliable


- Opto-Electrical Detecting, delivers accurate detection even when notes are severely degraded.
- High security cassettes and a separate reject tray with lock and seal-leading.
- Unique log record and inquiry function, enables to record and check every transaction.
- Unique self-calibrating function, automatically compensates for assembling errors.
- Offline diagnosis system enables convenient troubleshooting.

- Auto retract function
- Flexible
- Modular design, easy to assemble and disassemble
- Front or rear service access for convenient maintenance
- Optional long throat for the presenter
- High process speed and capacity
- Friction feed, able to handle various currencies
- Dispensing at a high speed of 7 notes/ second
- Maximum 3,000 fit notes per cassette, expandable up to 6 cassettes, 18,000 fit notes in total


Specifications

- **Media ranges**
Length: 110mm ~172 mm
Width: 55mm ~85 mm
Thickness: 0.06mm ~0.18 mm
Dispensing system: Friction feed, Bundle dispensing, 7 notes/second
Maximum notes per transaction: 60 notes
Low level detection: 50~250 notes (adjustable)
Reject mode: Single/Bundle
Maintenance: Front/Rear
- **Note Cassette**
Expandability: Up to 6 Cassettes capacity: 3,000 fit notes per cassette
Reject tray capacity: 100 (for unfit note reject) + 250 (for forgotten note reject)
Security: Mechanical lock and lead sealing
- **Weight**
standard throat: 42 Kg long throat: 44 Kg (two cassettes weight, with the increase of every cassette, the weight shall be added by 11kg.)
Communication interface: RS-232/ USB (optional)
Operating environment: Temperature: 00C~500C Humidity: 20%~90% non-condensing
- **Power supply**
Voltage: 24V+/-10%,
Consumption: Maximum 200W, Idle 30W, Operating 100W

Dimensions



Front Service standard throat



Rear service, standard throat

The dimensions above are based on 2 cassettes height, with the increase of every cassette, the height shall be added by 142.5mm

GRGBanking Equipment Co., Ltd

Add: 9 Kelin Road, Science City, Luogang District, Guangzhou, China 510663
Tel: +86 20 8218 9249
Fax: +86 20 8218 8163
Email: oem@grgbanking.com

Copyright by GRGBanking Equipment Co., Ltd.
All rights reserved@201211MD02

Specifications are subject to update without prior notice.
Please consult GRGBanking or its representative for the latest information.